



Technical data

| Type | Catros 3001 Catros ⁺ 3001 | Catros 3501 Catros ⁺ 3501 | Catros 4001 Catros ⁺ 4001 | Catros 4001-2 Catros ⁺ 4001-2 | Catros 5001-2 Catros ⁺ 5001-2 | Catros 6001-2 Catros ⁺ 6001-2 |
|---|---|---|---|---|---|---|
| Working width (m) | 3.00 | 3.50 | 4.00 | 4.00 | 5.00 | 6.00 |
| Power requirement from (kW/PS) | 66/90 | 77/105 | 91/125 | 91/125 | 110/150 | 130/180 |
| Disc diameter (mm) | Catros 460 / Catros ⁺ 510 | | | | | |
| Disc spacing (mm) | 250 | | | | | |
| Number of discs | 2 x 12 | 2 x 14 | 2 x 16 | 2 x 16 | 2 x 20 | 2 x 24 |
| Working depth (cm) | 3 – 12 | 3 – 12 | 3 – 12 | 3 – 12 | 3 – 12 | 3 – 12 |
| Setting the disc stagger | Mechanical via offset slide | | | | | |
| Transport length with lighting (m) | 2.45 | 2.45 | 2.45 | 2.65 | 2.65 | 2.65 |
| Transport width (m) | 3.00 | 3.50 | 4.55 | 2.95 | 2.95 | 2.95 |
| Transport height (m) | 1.70 | 1.70 | 1.70 | 2.50 | 3.00 | 3.50 |
| Weight (kg) Catros/Catros ⁺ (base machine, road lights, mech. depth adjustment, cage roller) | 1438/ 1478 | 1560/ 1610 | 1708/ 1758 | 2720/ 2770 | 2910/ 2970 | 3095/ 3170 |

| Type | Catros 3002-T Catros ⁺ 3002-T | Catros 3502-T Catros ⁺ 3502-T | Catros 4002-T Catros ⁺ 4002-T | Catros 5501-T Catros ⁺ 5501-T | Catros 7501-T Catros ⁺ 7501-T | Catros 4001-2 TS Catros ⁺ 4001-2 TS | Catros 5001-2 TS Catros ⁺ 5001-2 TS | Catros 6001-2 TS Catros ⁺ 6001-2 TS |
|--|---|---|---|---|---|---|---|---|
| Working width (m) | 3.0 | 3.50 | 4.0 | 5.50 | 7.50 | 4.0 | 5.0 | 6.0 |
| Power requirement from (kW/HP) | 60/80 | 74/100 | 90/120 | 125/170 | 160/240 | 91/125 | 110/150 | 130/180 |
| Disc diameter (mm) | Catros 460/Catros ⁺ 510 | | | | | | | |
| Disc spacing (mm) | 250 | | | | | | | |
| Number of discs | 2 x 12 | 2 x 14 | 2 x 16 | 2 x 22 | 2 x 30 | 2 x 16 | 2 x 20 | 2 x 24 |
| Working depth (cm) | 3 – 12 | 3 – 12 | 3 – 12 | 3 – 12 | 3 – 12 | 3 – 12 | 3 – 12 | 3 – 12 |
| Setting the disc stagger | Mechanical via offset slide | | | | | | | |
| Linkage | Lower linkage | | | Swinging drawbar, straight drawbar or lower link arms | | Lower linkage | | |
| Roller | Wedge ring roller | | | Wedge ring tyre roller | | wedge ring tyre roller | | |
| Transport length with lighting (m) | 4.50 | 4.50 | 4.50 | 5.60 | 5.60 | 6.30 | 6.30 | 6.30 |
| Transport width (m) | 3.00 | 3.55 | 4.55 | 3.00 | 3.00 | 2.95 | 2.95 | 2.95 |
| Transport height (m) | 1.90 | 1.90 | 1.90 | 3.00 | 4.00 | 2.80 | 3.30 | 3.80 |
| Weight (kg) Catros/Catros ⁺ (base machine, road lights, mech. depth adjustment, roller) | 2100/ 2140 | 2450/ 2500 | 2800/ 2850 | 4800/ 4870 | 5900/ 5970 | 3620/ 3670 | 3810/ 3870 | 3995/ 4070 |

Illustrations, content and technical data are not binding! Machine illustrations can vary due to country-specific traffic legislation. For specific road traffic specifications, please refer to the instruction manual.

