



Technical data

	ED 4500-C rigid	ED 6000-C rigid	ED 4500-2C folding	ED 6000-2C folding	ED 6000-2FC folding		ED 12000-KR	
Execution	Special	Special	Special	Special	Super	Special	Super	Special
Working width (m)	4.20–4.80	5.40–6.40	4.20–4.80	5.40–6.40			12.60	
Number of sowing units	6, 8	8–12	6, 7	8, 9		8, 12		18, 21
Possible row spacing (cm)	70, 75					45, 50, 70, 75		
Sowing units	Contour or Classic							
Tyre options	10.0/75-15			31x15.5/15			10.0/75-15 (KR = 550/60-22.5)	
Transport width (m) on 75 cm row spacing	4.06	6.00	3.00	3.00			5.80	
Transport width (m) depending on the row spacing	4.00–4.31	5.40–6.40	3.00	3.00–3.25			5.80	
Transport length (m)	2.40–2.60	2.90–3.10	2.80–3.00	2.90–3.10			11.40	
Singling drive	mechanical			mech.	hyd.	mech.	hyd.	mechanical
Seed spacing	3.1 cm to 86.9 cm depending on the singling disc used							
Blower fan drive	PTO shaft with over-run clutch, PTO input speed 540 min ⁻¹ , 710 min ⁻¹ or 1,000 min ⁻¹ Optional hydraulic blower fan drive (not for ED 6000-C Special)						hydraulic	
Singling unit	Singling discs for maize, sunflowers, sugar beet, rape, soya, sorghum, field beans, peas							
Fertiliser hopper capacity (l)	900	1,100	900/1,100	1,100		1,500–2,000		–
Drive: fertiliser metering	mechanical			mech.	elect.	mech.	elect.	–
Filling height: fertiliser hopper (m)	1.78	1.91	1.78/1.91	1.91		1.60/1.78		–

Illustrations, content and technical data are not binding! Technical data may deviate according to the level of equipment.
Machine illustrations can vary due to country-specific traffic legislation.



AMAZONEN-WERKE H. Dreyer GmbH & Co. KG
P. O. Box 51 · 49202 Hasbergen-Gaste/Germany
Phone +49 (0)5405 501-0 · Fax +49 (0)5405 501-193