



## Technical data EDX

Model	EDX 6000-TC	EDX 9000-TC
Working width (75 cm row spacing)	6 m	9 m
Transport width	3 m	3 m
Forward speed range	8 to 15 km/h	
Fertiliser hopper capacity	3,000 l	4,600 l
Seed hopper capacity	600 l	2 x 400 l
Number of sowing units (75 cm row spacing)	8	12
Possible row spacings in (cm)	37,5, 44,9 (45), 50, 55, 70, 75, 80	44,9 (45), 50, 55, 70, 75, 80
Max. sowing units with under root fertilisation	16	20
Power requirement	from 125 kW /170 HP	from 180 kW /250 HP
Min. electric requirement	12.5...13 V / 30 A ((tractor alternator >110 Ah)	12.5...13 V / 30 A ((tractor alternator >150 Ah)
Min. hydraulic requirement	80 l/min at 180 bar	120 l/min at 190 bar
Hyd. connections	2DA+1SA with pressure-free return	

Illustrations, content and technical data are not binding! Deviations of technical data are possible depending on the equipment. The illustrations may deviate from the requirements for local road traffic regulations.



**AMAZONEN-WERKE H. DREYER GmbH & Co. KG**  
P. O. Box 51 · D-49202 Hasbergen-Gaste/Germany  
Phone: +49 (0)5405 501-0 · Fax: +49 (0)5405 501-193